

INSTRUCTIONS FOR USE



Terrace pool Prime

Wood fired



Thank you for choosing us as your terrace pool supplier

We hope the terrace pool will give you many lovely baths and pleasant moments. For the best conditions for lifelong durability, we recommend that you read through the user manual before you start using your new terrace pool. This instruction manual applies to the Prime terrace pool and will describe what is important to consider before, during and after your swim. More information is available under the swimming school at svenskabadtunnor.se. If you have any questions, you are welcome to contact us at info@svenskabadtunnor.se.

BUILT-IN

THE UNDERWORK

The foundation is an important part of the installation as the terrace pool with water and many bathers can reach weights of over 1500 kg. The part-time work differs slightly depending on the conditions you have. Usually it is built on earth or gravel and then it may be necessary to dig out a piece and lay out a ground cloth. If you are building on rock or stone, you can build with regular timber directly on top. Make sure to place the terrace pool at a level level and on a firm surface.

SUPPORT

The terrace pool is made of polyethylene plastic, which is a movable material, so it is very resistant to shocks and cold. Because it is not mute, it needs a support under the seating surfaces, this is important as otherwise there will be too much load and it will not keep its shape. On our website there is a drawing of a bottom support that can be built yourself. Alternatively, ready-made bottom support can be bought in cellular plastic, it is also possible to buy with ready-made walls in cellular plastic, no additional support needs to be built if you choose this solution.

INSULATION

Before you build in the terrace pool, you should think about whether insulation is relevant for you. It depends a little on how you intend to use the terrace pool. If you are going to bathe a lot in winter or keep the water in the bath for a long time, we recommend that you insulate with at least 50 mm of cellular plastic (preferably 70-100 mm). An instructional video on an example of how you can insulate is available on our YouTube channel. Alternatively, our ready-made insulation package can be ordered on the website, made of EPS S100 cellular plastic 85 mm.

RECEIPT OF DELIVERY

Check that no transport damage has occurred during delivery. If this has occurred, read further instructions during open purchase. Lift the lid and then remove all cardboard and loose parts from the terrace pool.


Then fold down the terrace pool so that it stands with the bottom on the ground. Remove the conveyor belts, the pallet and the protective packaging.

Check that all the following parts are included:

- Stove
- 2 meter hose
- 2 m Flue pipe
- 4 hose clamps
- 2 connections
- Insulated cover

Before you fill the terrace pool with water for the first time, it should be rinsed and dried as assembly dust and dirt often remain after assembly in the factory.

Make sure the upper hose slopes slightly upwards towards the terrace pool and the lower hose is straight. This is important for self-circulation to work. It is recommended not to place the stove more than about 1 meter from the terrace pool. After that, self-circulation will slow down. Optimally, the stove is placed between 20-50 cm from the terrace pool.



INSTALLATION OF THE TERRACE POOL

1. If you have bought our ready-made insulation, you install the insulation first. You can see how to install the insulation on our installation video on the website. Alternatively, you build your own support.
2. Mount the connections according to the separate manual.
3. If you have ordered lighting for the bath, install it according to the separate manual.
4. Carefully lift into the bath in the insulation.
5. Build your bath to your liking. The bath must be placed on a flat and stable surface.
6. Mount the four clamps to the lid with the included screws. The code for the lid is 00. It cannot be changed.

MAINTENANCE

THE TERRACE POOL

- The plastic is wiped clean with a wet cloth and a little mild detergent without surfactants if necessary.
- The stove is preferably emptied of ash with an ash shovel or coarse vacuum cleaner.

THE BATH WATER

We recommend our customers, who do not have a bath equipped with a purification system, to change the bath water between each bathing occasion. If you do not have the opportunity to do this and choose to use the bath water more than once, there are some simple tricks to maintain good water hygiene.

- Always shower before going into the bath to avoid contaminating the bath water with sun lotion and skin particles. This should also be done when using a treatment plant.
- Add germicide. It is important to **never** add a chlorine-based agent (or other disinfectants with corrosive content) as chlorine is not good for the skin, the environment or the stove. We recommend the chlorine-free disinfectant BioCool. Dosing is done easily according to the instructions on the bottle. Pool disinfection should also be used if a treatment plant is used.

The above advice increases the possibility of using the bathing water on more than one bathing occasion. Remember that circumstances such as weather conditions, the number of bathing occasions and the number of bathers are decisive for how long the bathing water can be kept hygienic.

In order not to risk your stove being attacked by corrosion, you need to measure the pH, alkalinity and hardness of your water.

THE PH VALUE

Rätt pH-värde är grundläggande för en bra vattenkvalité. Därför är det absolut nödvändigt att ställa in pH-värdet så att det ligger inom idealområdet 7,0 – 7,4. pH-värdet påverkar samtliga vattenvärden. Har du ett för högt eller lågt pH i ditt vatten så kan det orsaka korrosion på kaminen.

HARDNESS

The ideal total hardness is 150 – 250 mg/l. Water with a very low degree of hardness can be very aggressive. Metal parts corrode and the surface can be attacked.

If the water is hard, there is a risk of lime deposits and that the water in the spa bath may become cloudy and discolored. Lime and metal ions usually occur in a dissolved state in the water, but if the water is too hard, it can lead to deposits on the stove.

ALKALINITY

Too low alkalinity can make it difficult to set the correct pH. The optimal alkalinity value is between 80–120 mg/l.

SALTWATER

All the parts that are in direct contact with the bathing water are adapted for salt water. It is therefore perfectly possible to use salt water as bath water. Note, however, that the salt in the water can leave deposits, which can cause discolouration. Wipe exposed surfaces regularly to remove salt deposits.

WINTER USE

No guarantees apply if you leave water in the bath and the water freezes. If you have an insulated lid and insulated frame, however, it can take up to a month before the water freezes in the bath despite freezing temperatures. The water in the stove and hoses freezes faster than in the bath. Be sure to drain hoses and stove from water when it is freezing outside.

SACRIFICE ANODE

The stove is equipped with a magnesium sacrificial anode. It is located at the bottom of your stove. The function of the sacrificial anode is that corrosion should occur on the anode instead of on your stove. It is therefore important that it is cleaned in case of corrosion. To see if the anode has been attacked, you unscrew it, no tools are needed, only hand power. The rod on the anode can then have a coating. If it does, scrape off the coating with a knife/sandpaper. The surface must be metal clean.

In the case of heavy or repeated coating, the anode will eventually need to be replaced. The smaller the anode, the worse the function. The anode must be at least 10 mm in diameter and 90 mm long. Contact us at info@svenskabadtunnor.se to order a new magnesium rod.

HEATING

This chapter will cover important points to consider before, during and after you fire. Before you start a fire in your stove, it is important that you fill the hot tub completely with water, a minimum of 15 cm from the top edge of the hot tub. This is extremely important as you otherwise risk burning the stove or the plastic as it overheats if there is no water in the hot tub. In order to get the most efficient heating possible, it is recommended that the hot tub be heated with a lid on it. Remember to stop the fire in time. The stove after heats very well and it is easy for the water to get too hot. If it still happens, you can lower the temperature a few degrees by adding cold water.

LIGHT THE STOVE

When you make a fire, really dry birch wood is preferable. Split a handful of wood chips to light with, then split some logs into several smaller pieces. Put the wood chips in the stove and the smaller logs on top of them. Then light with caution. When the fire is lit, it is important to burn actively to bring up the right bath temperature (recommended temperature is 38 degrees). Add one or two logs at a time at the beginning so as not to smother the fire. Then you can fill up a lot of wood and have an active fire in the stove. For more fire tips go to the swimming school at svenskabadtunnor.se

WHEN YOU HAVE FINISHED BURNING

When you have finished bathing, it is important not to empty the water before the stove has cooled completely. If there is a risk of the water freezing, it is also important to empty the hot tub so that it does not freeze to pieces.

- The stove and flue become very hot during firing. Keep an eye on bathing children so they don't burn themselves.

- Keep in mind that sparks can fly when burning. If the hot tub is placed on something combustible, a heat shield of some kind may need to be used. Also consider this if the hot tub is placed close to property.

- Never leave children unattended in the terrace pool.

- Always check the water temperature before you or someone else jumps into the bath.

- Make sure that no unauthorized person can get into the bath without your knowledge.

OPEN PURCHASE & SHIPPING DAMAGE

We want to be sure you made the right choice. That's why you always have 15 days to buy with us. Open purchase assumes that you still have the original packaging and have not used the product. You are responsible for the return shipping, but get back the full amount for the product minus a deduction of SEK 2,000.

The product must be returned in its original condition. Deductions are made when returning a specially ordered product or damage.

If the terrace pool has received shipping damage, it is important that you photograph these before unloading from the transport truck. A signature by the driver on the delivery note is also necessary to receive any compensation.

Then send an email to info@svenskabadtunnor.se with pictures and an explanation of what happened.

Otherwise, the Consumer Purchase Act and the Distance Contracts Act are complied with. In the event of a dispute, we follow the recommendations of the General Complaints Board.

For more information, read our purchase conditions on the website.